



HARTING Cabinet Outlet RJ45, 8-poles
RJ45 distribution module for IP20 environments
(top-hat rail mounting)

Advantages

- Simple mounting
- Dust protection caps
- Port identification
- Angled output


Technical characteristics

Number of ports, Copper / Termination	1 / RJ45 (Twisted Pair)
Transmission performance	Category 6A / Class E _A up to 250 MHz acc. to ISO/IEC 11 801:2002, EN 50 173-1
Transmission rate	10/100 Mbit/s and 1/10 Gbit/s
Mounting	To 35 mm top-hat mounting rail acc. to DIN EN 60 715, alignable
Dimensions (H x W x D)	71 x 18 x 68 mm
Degree of protection	IP20
Operating temperature range	-20 °C ... +70 °C
Housing material	Polyamide, UL94 V-0
Colour	Grey

Identification	Part number	Drawing	Dimensions in mm
----------------	-------------	---------	------------------


**HARTING RJ Industrial®
Cabinet Outlet RJ45**

09 45 851 0000



**Protection cover set
for 09 45 851 0000**

09 45 851 0001



Usable RJ45 cable jacks

- Ha-VIS preLink® keystone set AWG 22/23 (with Ha-VIS preLink® terminal block) 20 82 501 0001
- Ha-VIS preLink® keystone set (without Ha-VIS preLink® terminal block) 20 82 500 0001

Usable with Ha-VIS preLink® terminal blocks

- Ha-VIS preLink® terminal block AWG 22/23 (24) 20 82 000 0001
- Ha-VIS preLink® terminal block AWG 26/27 20 82 500 0003

Usable RJ45 cable jacks

- RJ45 keystone module IDC AWG 24 – AWG 22 09 45 545 1564
- RJ45 keystone module IDC AWG 27 – AWG 26 09 45 545 1563