


# **OSI LaserDiode**

# 905nm Pulsed Laser Diode

### **Single Mode Pulsed Instrument Laser Modules**

The 905nm pulsed laser offers a far-field beam pattern with equivalent divergence values for both the Fast (Perpendicular) and the Slow (Parallel) Axes of emission. The adjusted Far Field pattern offers higher coupling efficiency into standard spherical lens systems. The laser/lens is hermetically sealed in a 9mm package that offers robust environmental survival capability for demanding applications such as field-deployed range finders. This product is RoHS compliant.







## Typical Electro-Optical Specifications at T<sub>A</sub>=25 °C

Parameter	Symbol	Min	Тур	Max	Unit
Wavelength	λ	893	903	913	nm
Spectral Width FWHM	Δλ		8		nm
Temp Coeff. of Wavelength	Δλ / ΔΤ		0.24		nm / °C
Peak Power	$P_{o}$	75	87		W
Pulse Width	PW		100		nS
Duty Factor	DF		0.1		%
Drive Current	-		30		Α
Beam Divergence (FWHM)	-		8 x 8		Deg.
Storage Temperature	T <sub>s</sub>	-40		+85	°C
Operating Temperature	T <sub>o</sub>		25		°C

### **Amplitude Normalized (Relative Units)**





### **Amplitude Normalized (Relative Units)**





### **Mechanical Specifications**

Units are in inches (mm)











### Warranty

Please refer to your product purchase agreement for complete details or check with your OSI LaserDiode sales representative.

### **Safety**

- Caution: Laser light emitted from any diode laser may be harmful to the human eye.
- Avoid looking directly into the diode laser aperture when the device is in operation.

### Class 3B laser

### **ESD Caution**

Handle diode lasers with extreme care to prevent electrostatic discharge. Follow ESD precautions when handling devices.

### **Legal Disclaimer**

Information in this data sheet is believed to be correct and reliable. However, no responsibility is assumed for possible inaccuracies or omission. Specifications are subject to change without notice.



